



## PRODUCT OVERVIEW

The new Gate Valve Safety Device is quickly driving industry safety standards forward through innovation.

Producers are faced with many ongoing daily challenges, one of those being fluid transfer from tank to truck. Many risks are involved including physical, property and environmental. Eliminating the risk of accidental hose disconnect when transferring fluid ends up saving money. The Gate Valve Safety Device is designed and engineered to do just that. With it's patented design the GVSD is easy to install, use and maintain.

## KEY FEATURES

- Reduces oil spills on site due to accidental valve opening or suction hose disconnections
- Greatly improves safety for transportation companies and operators
- Rugged design
- Extremely simple operation
- No safety bypass
- Quick installation
- Minimum of 1/4" mild steel construction
- Easily mounts to existing gate valve
- Tight foot print to the valve making it easy to install in tight places
- Smooth, one-hand operation
- Includes mounting hardware

## SPECIFICATIONS

		DIMENSIONS	SPECIFICATIONS	
	Dimension A	25.125"	Operational Applications	All transportation related applications
	Dimension B	4.875"		
	Dimension C	14.50"	Material	Minimum of 1/4" mild steel
	Dimension D	1.875"		
	Dimension E	11.00"	Patent Number	Pending

1 855 PRO FIRE | [www.profireenergy.com](http://www.profireenergy.com)

# PROFIRE

**CANADA- Alberta**  
 Box 3313  
 Bay 12, 55 Alberta Ave  
 Spruce Grove, AB T7X 3A6

**USA-Utah**  
 321 S 1250 W  
 Suite 1  
 Lindon, UT 84042

**USA-Texas**  
 19407 Park Row  
 Suite 100  
 Houston, TX 77084

**USA-Texas**  
 305 Sam Houston Dr.  
 Unit E  
 Victoria, TX 77901

**USA-Oklahoma**  
 4334 NW Expressway  
 Suite 281  
 Oklahoma City, OK 73116

**USA-Pennsylvania**  
 18815 Route 287  
 Tioga, PA 16495